



The Kitty Tube™ Awning and Vent Cap Instructions



Pic. 1 and 2 and 3

If foam gasket is not already installed on awning, install as shown in Picture 1, 2, and 3.



Pic. 4

Place awning with gasket into opening making sure gasket is on the outside, and tabs on bottom are on the inside of the Kitty Tube as shown in black circle.



Pic. 5

Lift upwards on the awning so it tilts into the opening.



Pic. 6 and 7 and 8

You can either remove the foam wrapper (recommended), or it can be pulled back as shown in Pic. 6 to install the horseshoe retainer. While lifting up slightly on the front edge of the awning to lightly compress the gasket, start the horseshoe retainer into the top awning groove protruding into the Kitty Tube. After starting into the groove, slide downward evenly until it is solidly engaged.

NOTE: If the horseshoe retainer is not pushed down evenly, one leg of the horseshoe might feel loose when pushing up/down on the top tab. To fix this, disengage and move the opposite leg upward one tooth (see removal instructions on how to disengage) after releasing one retainer tooth on the opposite leg, push down on the loose leg, and it will seat firmly. There should be no movement in the horseshoe part if installed correctly.




Pic. 9

To remove awning, pull out on tabs as shown in Pic. 9 to disengage the horseshoe retainer.



Pic. 10 and 11

To install the clear flap door, simply place slots over tabs on horseshoe retainer. After placing over tabs, make sure flap door is slid downward to lock onto tabs.



Pic. 12

IMPORTANT: As shown in Pic. 12, push top of clear flap door underneath top horseshoe retainer tab to lock flap door into place. To remove, reverse steps.



Pic. 13

Vent Cap installation. If gasket is not pre-installed, slide gasket onto vent cap as shown in Pic. 13.

We also have video tutorials at www.thekittytube.com

Contact or visit us at www.thekittytube.com with any other questions or concerns.

Sincerely,
Jim Bradac - Inventor / President / Owner



Pic. 14

Start vent tabs into hole in top of lid as shown in Pic. 14




Pic. 15


Push downward firmly until vent cap snaps into place completely as shown in Pic. 15



Kitty Tube LLC
579 Schommer Dr.
Hudson Wi. 54016
Office. 715-377-2133
Fax. 715-377-2135
www.thekittytube.com



With the Kitty Tube lid upside down, line up the awning with the hole in the lid as shown in picture A.



Slide awning through hole in lid, and start only one of the curved ends into the slot on the awning as shown on Picture B.



Pushing the awning with your thumbs, while putting your fingers on the outside of the lid, work the awning from the started end to the other end until it snaps all the way into the groove as shown on Picture C.

We also have video tutorials at www.thekittytube.com